

FIRST CHOICE

Santanna II

BLOWER



FEATURES

- Side or bottom mount
- Heat-free due to open air system that eliminates back pressure build-up
- Internal check valve resists water damage
- Mounting body is Hi-Temp material
- Side/Bottom outlet is perfect for any outdoor installation; slip plug is included for the outlet that is not in use
- Protected for the locked motor condition
- Has been tested, certified and listed by UL to requirements of both UL and CSA standards
- First Choice Air Blowers for residential use are backed by a full one-year, no water damage, warranty
- Bracket on case for easy mounting
- High impact strength construction
- Indoor/outdoor use

FIRST CHOICE Air Blowers

Part No.	HP	Volts	Amps	Orifice Dia.	Air Flow (CFM)	PSI
FCH7503101280	1.0	110	7.0	2"	115	2.1
FCH7503102280	1.0	220	3.5	2"	113	3.8
FCH7503151280	1.5	110	8.0	2"	120	4.2
FCH7503152280	1.5	220	4.0	2"	108	2.1
FCH7503201280	2.0	110	9.0	2"	128	3.8
FCH7503202280	2.0	220	6.0	2"	119	4.2



807-8410-FCH.0518

Phone: 909-969-2255
 customerservice@firstchoicepool.com
 www.firstchoicepool.com



*Designed,
 Engineered &
 Manufactured
 in the USA.*

©2018 Waterway Plastics